

Cattle slats Doubles

Double cattle slats manufactured mostly for replacements. Manufactured 200 mm deep and designed for cattle loading or tractor loading to your required length up to 3660mm(12ft) long. Notched ends manufactured to match maxi slat depth of 178 mm. Slats designed to your length and load bearing requirements.

Design Features

- Cattle loading to 3660mm (12ft) long
- Tractor loading to 3660mm (12ft) long
- Mechanical installation required
- 200 mm thick or Notched end to 178 mm thick
- Designed to current BS EN standard
- Manufactured to customers specific length

Uses for Double slats

- Farm sheds replacements, new build
- Infill unit in an odd length of tank

Slat Type	Loading	Length	Width	Height
Double	4 tonne	1.8 - 3.66 m	0.33 m	0.2 m
Double	Cattle	1.8 - 3.66 m	0.33 m	0.2 m
Double N/E	4T Tractor	1.8 - 3.66 m	0.33 m	0.178 m
Double N/E	Cattle	1.8 - 3.66 m	0.33 m	0.178 m

Design & Quality Assurance provisions

- Design certificates available for your building warrants
- Concrete design certificates supplied
- Concrete strength cube reports available upon request

Contact Information

- E-mail - sales@solway-precast.co.uk
- Phone - 01465821348

