

Treble slats

Treble cattle slats are mostly for replacements but can also be used in new builds, 333mm wide and 200 mm deep, slats are designed for either cattle or tractor load bearing and can be manufactured to your required length up to 3660mm (12ft) long. Notched ends compatible with Maxi slat 178 mm available.

Design Features

- Cattle loading to 3660mm (12ft) long
- Tractor loading to 3660mm (12ft) long
- Mechanical installation required
- 200 mm thick or Notched end to 178 mm thick
- Designed to current BS EN standard
- Manufactured to customers specific length

Uses Treble slats

- Existing farm shed replacements
- Also used in new builds
- Infill unit in an odd length of tank

Slat Type	Loading	Length	Width	Height
Treble	4T Tractor	1.8 - 3.66 m	0.5 m	0.2 m
Treble	Cattle	1.8 - 3.66 m	0.5 m	0.2 m
Treble N/E	4T Tractor	1.8 - 3.66 m	0.5 m	0.178 m
Treble N/E	Cattle	1.8 - 3.66 m	0.5 m	0.178 m

Design & Quality Assurance provisions

- Design certificates available for your building warrants
- Concrete design certificates supplied
- Concrete strength cube reports available upon request

Contact Information

- E-mail - sales@solway-precast.co.uk
- Phone - 01465821348

