

Modular sectional slurry store

Underground modular slurry store is quick and easy to install, units come in standard 4572mm (15ft) or 6096mm (20ft) panels to create your tank size. Single width or multiple width tanks with support columns and beams available. This system removes the need to shutter tanks and with careful planning and organised deliveries can be erected in days, a crane normally required. Sealant strips are supplied for the tongue and grooved joints, requiring pointing when finished.

Design Features

- Panel sections come in 4572mm (15ft) or 6096mm (20ft) lengths
- Tank depth is 2360mm
- Quick and easy to install with a mobile crane
- Flood floor with ready-mix concrete to seal the tank
- Sealant strips supplied, comply with SEPA requirements
- Tongue and groove joint system to form a secure joint
- Designed to current BS EN standard
- Incorporated lifting socket for installation with a designed and certificated lifting devices
- Solway slats and passage slabs offer a full package for your tank

Uses for Modular slurry stores

- Underground slurry store within your shed project
- Underground slurry store

Tank size	Length	Width	Height	Volume M3
1 100ftx10ft	30.480 m	3.048 m	2.36 m	220 M3
2 100ftx20ft	30.480 m	6.096 m	2.36 m	440 M3
3 150ftx10ft	45.75m	3.048 m	2.36 m	330 M3
4 150ftx20ft	45.75 m	6.096m	2.36m	660 M3
5 200ftx13ft	61.00 m	4.000 m	2.36 m	573 M3

Design & Quality Assurance provisions

- Design certificates available for your building warrants
- Concrete design certificates supplied
- Concrete strength cube reports available upon request
- SEPA approved system
- Method statement for erection available

Contact Information

- E-mail - sales@solway-precast.co.uk
- Phone - 01465821348

